

netlife flex system; in-house project engineering or by customer; easy installation, extended functions and variable settings; easy commissioning per app, extended interconnectabilities

## CHARACTERISTICS

<b>Regiolux Classification</b>	netlife flex
<b>Control signal</b>	DALI broadcast, Radio
<b>Number of control gear (max)</b>	15
<b>Communication</b>	Bluetooth
<b>Sensor technology</b>	PIR - passive infrared
<b>Installation height (min/max)</b>	2m to 4m
<b>App name</b>	Hytronik Koolmesh
<b>System compatibility</b>	easy25, flex44, flex50, flex54, flex55, flex56
<b>Note</b>	Can be linked to further Hytronik Koolmesh controllers.
<b>System extension</b>	netlife flex54, netlife flex55
<b>Application</b>	Office, Corridors, Secondary rooms, Meeting rooms, Classrooms
<b>Function</b>	Motion detection, presence detection, Corridor function, Guided Light, HCL (only with DT8 luminaires), Tunable white (only with DT8 luminaires), Daylight control, Manual dimming



## MONITORING AREA

<b>Mounting Height</b>	3m	4m
<b>Ø max. sitting[S]</b>	4m	-
<b>Ø max. radial[R]</b>	4m	4m
<b>Ø max. tangential[T]</b>	7m	7m

