

Recessed downlight - Highly specular mirror reflector - direct wide distribution - IP 54

Housing made of sheet steel with cover ring made of diecast aluminium painted similar to RAL 7032 grit grey, with translucent diffuser made of safety glass, with driver wired ready for operation, aluminium heat sink for effective passive cooling. With mounting springs for installation without tools, suitable for ceiling thickness of 10mm-25mm. Housing colour pebble grey metallic; Light distribution direct wide distribution by means of Highly specular mirror reflector of High-purity aluminium, with translucent cover made of safety glass, UGR (4H/8H) 20.6. External driver with luminaire wired ready for operation. Electrical connection via 3-pole connection terminal with plug-in contacts.. With the Changy-SR VW accessory refurbishment ring, a ceiling cut-out of 230-300mm is possible.

CHARACTERISTICS

Order number	36941314125
EAN number	4020863354269
Commodity code	94051190
Certification mark	IP 54, Protection class II, F, Indoor, CE
Impact resistance (IK rating)	IK02
Ambient temperatur	ta 25°C
Warranty period	5 years

DEEP-LINK

<https://www.regiolux.de/en/article/36941314125>

ELECTRICAL ENGINEERING

Controller	Electronic driver (1 pcs.)
System output	10W
Mains voltage	230V/50Hz
Energy efficiency class/light source	D

LIGHTING TECHNOLOGY


Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 3000K
Colour tolerance (MacAdam)	3SDCM
Photobiological safety (Luminaire)	RG1
Nominal luminous flux	1135lm
LED service life	50000h L80/B10 (Tq 25°C)
Luminaire luminous efficiency	118lm/W
Beam angle	85°
UGR lat./long.	20.6 / 20.6

MECHANICS

Housing colour	pebble grey metallic
Dimensions (LxWxH/DxH)	246mm x 113mm
Depth	108mm
Ceiling system	cut-out ceilings [AD], Panel ceiling [PD] (module 100/200)
Ceiling cut-out (LxW/D)	229mm
Installation depth	165mm [AD]
Weight (net)	0.93kg
Type of installation	Ceiling installation individual mounting

Dimensions

H	113 mm	Height
D	246 mm	Diameter
T	108 mm	Depth
DA	229 mm	Cutting dimension diameter
DS min	10 mm	Ceiling thickness minimum
DS max	25 mm	Ceiling thickness maximum
Et(AD)	165 mm	Ceiling distance minimum (cut-out ceiling)
KL	157 mm	Length luminaire head or box for ballasts
KB	67 mm	Width luminaire head or box for ballasts
KH	30 mm	Height luminaire head or box for ballasts



Reference	LED 1100lm 830
ηLB	100 %
Φ ↓/↑	100 % / 0 %
UGR lat./long.	20.6 / 20.6

