

Wall luminaire - Single micro louvre with 80° lens - direct/indirect distribution

Sheet steel housing in square design; black, die-cast aluminium end faces; Housing colour silver grey/white aluminium RAL 9006; Light distribution direct/indirect distribution by means of Single micro louvre with 80° lens, à microparalume individuel noir, composante lumineuse indirecte homogène par diffuseur opalin en PMMA. 65° < 100 cd/m² according to current standard DIN-EN 12464-1. Electrical connection via 3-pole connection terminal with plug-in contacts.. Black available on request.

CHARACTERISTICS

Order number	60641034175
EAN number	4020863419890
Commodity code	94051190
Certification mark	IP 20, Protection class I, VDU 65°<100, F, Indoor, CE
Impact resistance (IK rating)	IK02
Ambient temperatur	ta 25°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

DEEP-LINK

<https://www.regiolux.de/en/article/60641034175>

ELECTRICAL ENGINEERING

Controller	Electronic driver (1 pcs.)
System output	15W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	55 pieces/B10, 90 pieces/B16, 65 pieces/C10, 100 pieces/C16
Energy efficiency class/light source	C

LIGHTING TECHNOLOGY


Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 3000K
Colour tolerance (MacAdam)	3SDCM
Photobiological safety (Luminaire)	RG1
Nominal luminous flux	2047lm
LED service life	50000h L80/B10 (Tq 25°C)
Luminaire luminous efficiency	134lm/W

MECHANICS

Housing colour	silver grey/white aluminium RAL 9006
Dimensions (LxWxH/DxH)	571mm x 76mm x 69mm
Weight (net)	1.8kg
Cable entry KE (X/Y)	90mm/0mm
Type of installation	Wall mounting

Dimensions

L	571 mm	Length
B	76 mm	Width
H	69 mm	Height
A1	430 mm	Mounting distance single mounting
X	90 mm	Distance cable infeed to the center of the luminaire on the X-axis
Y	0 mm	Distance cable infeed to the center of the luminaire on the Y-axis



Reference	LED 2000lm 830
ηLB	100 %
Φ ↓/↑	68 % / 32 %

