

## Accessories - Wire suspension

Rectangular canopy L=317mm, metal ceiling cylinder, 2 wires D=1.2mm L=1900mm, 2 cross-spans L=120mm, transparent connection cable Housing colour silver grey/transparent; Light Control: netlife flex10X; Regiolux Classification: netlife flex; Control signal: DALI, Radio; Number of control gear (max): 32; Communication: Bluetooth; App name: Casambi, 4remote BT; System compatibility: easy01S; flex10; flex10X; flex10L; flex37; flex39; Note: compatible with Casambi; Application: Office, Meeting rooms, Secondary rooms, Retail, Industry, Logistics centres, Corridors, Garages, Classrooms; Function: Motion detection\*, Corridor function\*, Guided Light\*, HCL (only with DT8 luminaires), presence detection\*, Daylight control\*, Tunable white (only with DT8 luminaires), Manual dimming, \*only by auxiliary devices.. With basicDIM wireless controller for DALI DT6, DT8, for hokal, procube, cubus LED/T5, lens basic, agila and kayak. Suspension set with integrated receiver, rectangular canopy, individual steel cable suspension with connection cable 5x0.75mm<sup>2</sup>, suitable for suspended luminaires with DALI controllers; With basicDIM wireless controller for DALI DT6, DT8, for hokal, procube, cubus LED, lens basic, agila and kayak. Operation and configuration via the Casambi app.

## CHARACTERISTICS

Order number	91231125135
EAN number	4020863422968
Commodity code	94059900
Certification mark	Indoor, CE

## DEEP-LINK

<https://www.regiolux.de/en/article/91231125135>

## ELECTRICAL ENGINEERING


Wiring	5x0.75mm <sup>2</sup>
--------	-----------------------

## MECHANICS

Housing colour	silver grey/transparent
Dimensions (LxWxH/DxH)	317mm x 44.5mm x 39mm
Weight (net)	0.6kg
Type of installation	Pendant individual mounting, Pendant light strip mounting, Pendant light structure

## Dimensions

L	317 mm	Length
B	44.5 mm	Width
H	39 mm	Height



## LC SYSTEM

### CHARACTERISTICS

<b>Regiolux Classification</b>	netlife flex
<b>Control signal</b>	DALI, Radio
<b>Number of control gear (max)</b>	32
<b>Communication</b>	Bluetooth
<b>App name</b>	Casambi, 4remote BT
<b>System compatibility</b>	easy01S; flex10; flex10X; flex10L; flex37; flex39
<b>Note</b>	compatible with Casambi
<b>Application</b>	Office, Meeting rooms, Secondary rooms, Retail, Industry, Logistics centres, Corridors, Garages, Classrooms
<b>Function</b>	Motion detection*, Corridor function*, Guided Light*, HCL (only with DT8 luminaires), presence detection*, Daylight control*, Tunable white (only with DT8 luminaires), Manual dimming, *only by auxiliary devices

