

Suspended luminaire/light run feed luminaire - Single micro louvre with 80° lens - direct/indirect distribution

Housing of sheet steel in a delicate square design; black, die-cast aluminium end faces; Housing colour silver grey/white aluminium RAL 9006; Light distribution direct/indirect distribution by means of Single micro louvre with 80° lens, with single micro louvre, black, homogeneous indirect share with opal diffuser made of PMMA. Suitable for VDU workstations, 65° < 100 cd/m<sup>2</sup> omnidirectional glare reduction in accordance with current DIN-EN 12464-1 standard, UGR (4H/8H) 15.8. Electrical connection via integrated transparent connection cable 3x0.75mm<sup>2</sup>, length 1900mm, stripped cable ends. Complete height-adjustable suspension set with canopy is included in delivery. Black housing and white single micro louvre possible on request.

**CHARACTERISTICS**

Order number	60615044175
EAN number	4020863419623
Commodity code	94051190
Certification mark	IP 20, Protection class I, $\gamma$ 65° < 100 cd/m <sup>2</sup> , F, Indoor, CE
Impact resistance (IK rating)	IK02
Ambient temperatur	ta 25°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

**ELECTRICAL ENGINEERING**

Controller	Electronic driver (1 pcs.)
Wiring	3x0.75mm <sup>2</sup>
System output	35W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	15 pieces/B10, 25 pieces/B16, 26 pieces/C10, 42 pieces/C16
Energy efficiency class/light source	B

**LIGHTING TECHNOLOGY**

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
Colour tolerance (MacAdam)	3SDCM
Photobiological safety (Luminaire)	RG1
Nominal luminous flux	4923lm
LED service life	50000h L80/B10 (Tq 25°C)
Luminaire luminous efficiency	142lm/W
UGR lat./long.	15.8 / 15.7

**MECHANICS**


Housing colour	silver grey/white aluminium RAL 9006
Dimensions (LxWxH/DxH)	1411mm x 51mm x 69mm
Weight (net)	3.7kg
Type of installation	Pendant individual mounting, Pendant light strip mounting

**Dimensions**

L	1411 mm	Length
B	51 mm	Width
H	69 mm	Height
A1	1200 mm	Mounting distance single mounting
P min	150 mm	Minimum suspension length
P max	1900 mm	Maximum suspension length

**DEEP-LINK**

<https://www.regiolum.de/en/article/60615044175>



Reference	LED 4900lm 840
$\eta_{LB}$	100 %
$\Phi_{\downarrow/\uparrow}$	73 % / 27 %
UGR lat./long.	15.8 / 15.7

