

Pendant luminaire - Micro-prismatic diffuser - direct/indirect distribution - with edge brightening

Extremely flat luminaire housing, designed by BUSSE Design+Engineering GmbH, extruded aluminium profile, natural anodised, visible installation height 23 mm; rounded natural anodised aluminium end faces, high stability due to cross braces made of stainless steel; Housing colour natural anodised aluminium; Light distribution direct/indirect distribution by means of Micro-prismatic diffuser of PMMA, Indirect component and longitudinally structured and luminous sides via cover made of frosted polycarbonate foil as dust protection, high luminous flux with direct and indirect component in lumen ratio 2:1; neutral white light colour (830) in direct and indirect component with very good colour consistency and high colour rendering Ra > 80. Suitable for VDU workstations, 65° < 3000 cd/m² omnidirectional glare reduction in accordance with current DIN-EN 12464-1 standard, UGR (4H/8H) 16.3. Two DALI LED drivers integrated, dimmable for direct and indirect component using commercially available switches. Electrical connection via integrated transparent connection cable 5x0.75mm², length 1900mm, stripped cable ends. Y-wire suspension with translucent connection cable and ceiling canopy included in the scope of delivery Switches must be provided by the customer.

CHARACTERISTICS

Order number	42161416570
EAN number	4020863289776
Commodity code	94051190
Certification mark	IP 20, Protection class I, γ 65° < 3000 cd/m², F, Indoor, CE
Impact resistance (IK rating)	IK03
Ambient temperatur	ta 25°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

ELECTRICAL ENGINEERING

Controller	Electronic driver dimmable via pushbutton (2 pcs.)
Wiring	5x0.75mm²
System output	56W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	13 pieces/B10, 24 pieces/B16, 25 pieces/C10, 40 pieces/C16
Energy efficiency class/light source	C

LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K+4000K
Colour tolerance (MacAdam)	3SDCM
Nominal luminous flux	8898lm
LED service life	50000h L80/B10 (Tq 25°C)
Luminaire luminous efficiency	159lm/W
UGR lat./long.	15.5 / 16.3

MECHANICS


Housing colour	natural anodised aluminum
Dimensions (LxWxH/DxH)	1394mm x 309mm x 41mm
Weight (net)	5.4kg
Type of installation	Pendant individual mounting

Dimensions

L	1394 mm	Length
B	309 mm	Width
H	41 mm	Height
A1	750 mm	Mounting distance single mounting
P min	150 mm	Minimum suspension length
P max	1900 mm	Maximum suspension length

DEEP-LINK

<https://www.regiolum.de/en/article/42161416570>



Reference	LED 8900lm 840/840
ηLB	100 %
Φ ↓/↑	65 % / 35 %
UGR lat./long.	15.5 / 16.3
VDU	65° < 3000cd/m²

