

Pendant luminaire - Silky matt MIRO-SILVER® micro-parabolic louvres - direct/indirect distribution - equipped for light run installation

Sheet steel housing, flat rectangular cross section, visible installation height 26 mm, end faces made of steel, prepared for light run installation; Housing colour silver grey/white aluminium RAL 9006; Light distribution direct/indirect distribution by means of Silky matt MIRO-SILVER® micro-parabolic louvres of aluminium, Reflectivity-enhanced parabolic aluminium louvre, silk matt, with low installation height cross blades, self-engaging. Suitable for VDU workstations, 65° < 1500 cd/m² omnidirectional glare reduction in accordance with current DIN-EN 12464-1 standard, UGR (4H/8H) 17.9. Electrical connection via 3-pole connection terminal with plug-in contacts.. Required accessories: Y-wire suspension for/without electrical connection must be ordered separately. Recommended minimum pendant length 0.5 m.

**CHARACTERISTICS**

Order number	60332024165
EAN number	4020863322305
Commodity code	94051190
Certification mark	IP 20, Protection class I, $\gamma$ 65° < 1500 cd/m², F, Indoor, CE
Impact resistance (IK rating)	IK03
Ambient temperatur	ta 25°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

**ELECTRICAL ENGINEERING**

Controller	Electronic driver (1 pcs.)
System output	43W
Mains voltage	230V/50Hz
Circuit breakers (inrush current)	15 pieces/B10, 25 pieces/B16, 24 pieces/C10, 38 pieces/C16
Energy efficiency class/light source	B

**LIGHTING TECHNOLOGY**

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
Colour tolerance (MacAdam)	3SDCM
Nominal luminous flux	5514lm
LED service life	50000h L80/B10 (Tq 25°C)
Luminaire luminous efficiency	129lm/W
UGR lat./long.	17.9 / 17.1

**MECHANICS**



Housing colour	silver grey/white aluminium RAL 9006
Dimensions (LxWxH/DxH)	1240mm x 198mm x 37mm
Weight (net)	4.113kg
Type of installation	Pendant individual mounting, Pendant light strip mounting

**Dimensions**

L	1240 mm	Length
B	198 mm	Width
H	37 mm	Height
A1	1216 mm	Mounting distance single mounting
A2	1279 mm	Mounting distance 1st luminaire of the light run
A3	1342 mm	Mounting distance between luminaires in a light run arrangement
P min	150 mm	Minimum suspension length
P max	1900 mm	Maximum suspension length

**DEEP-LINK**

<https://www.regiolux.de/en/article/60332024165>



Reference	LED 5500lm 840
$\eta_{LB}$	100 %
$\Phi_{\downarrow/\uparrow}$	62 % / 38 %
UGR lat./long.	17.9 / 17.1
VDU	65° < 1500cd/m²

