

Variable Device mount functional module netlife light management

Device mount made of a galvanised, profiled steel sheet; surface with polyester resin enamel coating; with two rotary catches for rapid fitting in the mounting rail, for the integration of sensors and control unit in the light run; can be positioned variable on the mounting rail. Housing colour black RAL 9005; . Electrical connection by means of a 0.7m connection cable for variable device mount positioning in the light run with freely positionable phases. Light Control: netlife easy24; Regiolux Classification: netlife easy; Control signal: DALI2 (Part 303, 304), Slave signal; Communication: Wired; Sensor technology: PIR - passive infrared; Installation height (min/max): 4m to 14m; Monitoring area: max. D=20m; System compatibility: easy23, central DALI2 controller; DALI system power: 6mA; System extension: easy24; Application: Industry, Logistics centres, Corridors, Garages; Function: Motion detection, Daylight control. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

## CHARACTERISTICS

Order number	19150700244
EAN number	4020863466009
Commodity code	85365080
Certification mark	IP 20, Protection class I, F, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Special properties	Advanced Services

## ELECTRICAL ENGINEERING

Controller	easy24
Mains voltage	230V/50Hz

## MECHANICS



Housing colour	black RAL 9005
Dimensions (LxWxH/DxH)	765mm x 95mm x 88mm
Weight (net)	0.9kg
Type of installation	Mounting rail system installation, Ceiling-mounted light structure, Pendant light structure

## Dimensions

L	765 mm	Length
B	95 mm	Width
H	88 mm	Height

## DEEP-LINK

<https://www.regiolux.de/en/article/19150700244>



## LC SYSTEM

### CHARACTERISTICS

<b>Regiolux Classification</b>	netlife easy
<b>Control signal</b>	DALI2 (Part 303, 304), Slave signal
<b>Communication</b>	Wired
<b>Sensor technology</b>	PIR - passive infrared
<b>Installation height (min/max)</b>	4m to 14m
<b>System compatibility</b>	easy23, central DALI2 controller
<b>DALI system power</b>	6mA
<b>System extension</b>	easy24
<b>Application</b>	Industry, Logistics centres, Corridors, Garages
<b>Function</b>	Motion detection, Daylight control



### MONITORING AREA

<b>Mounting Height</b>	5m	10m	14m
<b>Ø max. sitting[S]</b>	-	-	-
<b>Ø max. radial[R]</b>	11m	14,5m	-
<b>Ø max. tangential[T]</b>	34,5m	28m	20m

