

Variable Device mount functional module netlife light management

Device mount made of a galvanised, profiled steel sheet; surface with polyester resin enamel coating; with two rotary catches for rapid fitting in the mounting rail, for the integration of sensors and control unit in the light run; can be positioned variable on the mounting rail. Housing colour traffic white RAL 9016; . Electrical connection by means of a 0.7m connection cable for variable device mount positioning in the light run with freely positionable phases. Light Control: netlife easy24; Regiolux Classification: netlife easy; Control signal: DALI2 (Part 303, 304), Slave signal; Communication: Wired; Sensor technology: PIR - passive infrared; Installation height (min/max): 4m to 14m; Monitoring area: max. D=20m; System compatibility: easy23, central DALI2 controller; DALI system power: 6mA; System extension: easy24; Application: Industry, Logistics centres, Corridors, Garages; Function: Motion detection, Daylight control. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. netlife easy system; straightforward in-house project engineering; easy installation; preset functions; simple commissioning via remote control, app, DIP switch, rotary knob, etc.

CHARACTERISTICS

Order number	19150700240
EAN number	4020863421428
Commodity code	90328900
Certification mark	IP 20, Protection class I, F, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Special properties	Advanced Services

ELECTRICAL ENGINEERING

Controller	easy24
Mains voltage	230V/50Hz

MECHANICS



Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	765mm x 95mm x 88mm
Weight (net)	0.9kg
Type of installation	Mounting rail system installation, Ceiling-mounted light structure, Pendant light structure

Dimensions

L	765 mm	Length
B	95 mm	Width
H	88 mm	Height

DEEP-LINK


<https://www.regiolux.de/en/article/19150700240>



LC SYSTEM

CHARACTERISTICS

Regiolux Classification	netlife easy
Control signal	DALI2 (Part 303, 304), Slave signal
Communication	Wired
Sensor technology	PIR - passive infrared
Installation height (min/max)	4m to 14m
System compatibility	easy23, central DALI2 controller
DALI system power	6mA
System extension	easy24
Application	Industry, Logistics centres, Corridors, Garages
Function	Motion detection, Daylight control



MONITORING AREA

Mounting Height	5m	10m	14m
Ø max. sitting[S]	-	-	-
Ø max. radial[R]	11m	14,5m	-
Ø max. tangential[T]	34,5m	28m	20m

