

Variable Device mount functional module netlife light management

Device mount made of a galvanised, profiled steel sheet; surface with polyester resin enamel coating; with two rotary catches for rapid fitting in the mounting rail, for the integration of sensors and control unit in the light run; can be positioned variable on the mounting rail. Housing colour traffic white RAL 9016; Electrical connection by means of a 0.7m connection cable for variable device mount positioning in the light run with freely positionable phases. Light Control: netlife easy49; Regiolux Classification: netlife easy; Control signal: Switch; Number of control gear (max): 400W LED; Communication: Wired; Sensor technology: PIR - passive infrared; Installation height (min/max): 4m to 14m; Monitoring area: max. 30m x 4m; Remote control: 84501101203; Optional remote control: 84501101200 +App; App name: Steinel smart remote; Application: Industry, Logistics centres, Corridors, Garages; Function: Motion detection, Switch. When used with 7-pole rail, the contacts in the device mount must be reconnected. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

CHARACTERISTICS

Order number	19150700490
EAN number	4020863449477
Commodity code	90328900
Certification mark	IP 20, Protection class I, F, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Special properties	Advanced Services

ELECTRICAL ENGINEERING

Controller	easy49
Mains voltage	230V/50Hz

MECHANICS



Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	765mm x 95mm x 88mm
Weight (net)	0.9kg
Type of installation	Mounting rail system installation, Ceiling-mounted light structure, Pendant light structure

Dimensions

L	765 mm	Length
B	95 mm	Width
H	88 mm	Height

DEEP-LINK


<https://www.regiolux.de/en/article/19150700490>



LC SYSTEM

CHARACTERISTICS

Regiolux Classification	netlife easy
Control signal	Switch
Number of control gear (max)	400W LED
Communication	Wired
Sensor technology	PIR - passive infrared
Installation height (min/max)	4m to 14m
Remote control	84501101203
Optional remote control	84501101200 +App
App name	Steinel smart remote
Application	Industry, Logistics centres, Corridors, Garages
Function	Motion detection, Switch



MONITORING AREA

Mounting Height	5m	10m	14m
Ø max. sitting[S]	-	-	-
Ø max. radial[R]	13,5x3,5m	27,5x3,5m	30x3,5m
Ø max. tangential[T]	13,5x3,5m	27,5x3,5m	30x3,5m

