

Variable LED device mount functional module for safe emergency luminaire - LED single-lens optics - direct, extremely wide distribution

Device mount made of a galvanised, profiled steel sheet; surface coated with polyester resin paint; toolless attachment with pressure locks integrated in the design, for the integration of emergency lighting or connection to a central battery. Variable position on the support rail. Housing colour black RAL 9005; Light distribution direct, extremely wide distribution by means of LED single-lens optics, UGR (4H/8H) 31.1. Electrical connection by means of a 0.7m connection cable for variable positioning of the device mount with a 5-pin, quick-fit plug connector in the light run and free phase pre-selection; With 3h emergency lighting battery; Luminaire status by visible status LED in luminaire (NL-B3); Luminous flux in emergency light mode 207 lm. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

## CHARACTERISTICS

Order number	19070001004
EAN number	4020863420421
Commodity code	94051190
Certification mark	IP 20, Protection class I, F, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE
Impact resistance (IK rating)	IK03 (5°C bis 25°C)
Ambient temperatur	ta 5°C to 25°C
Warranty period	5 years

## ELECTRICAL ENGINEERING

Controller	Electronic driver 3h emergency lighting (1 pcs.)
System output	4W
Mains voltage	230V/50Hz

## LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 70 / 6000K
Colour tolerance (MacAdam)	7SDCM
Photobiological safety (Luminaire)	RG1
Nominal luminous flux	207lm
Nominal luminous flux-emergency lighting mode	207lm
Luminaire luminous efficiency	52lm/W
Beam angle	110° (C0) / 110° (C90)
UGR lat./long.	31.1 / 31.1

## MECHANICS


Housing colour	black RAL 9005
Dimensions (LxWxDxH)	765mm x 55mm x 35mm
Weight (net)	0.85kg
Type of installation	Mounting rail system installation, Ceiling-mounted light structure, Pendant light structure

## Dimensions

L	765 mm	Length
B	55 mm	Width
H	35 mm	Height

## DEEP-LINK

<https://www.regiolux.de/en/article/19070001004>



Reference	LED 200lm 760
ηLB	100 %
Φ ↓/↑	100 % / 0 %
UGR lat./long.	31.1 / 31.1

