

Device mount functional module universal 3-phase track

Device mount with integrated universal 3-phase conductor rail with DALI (useable length 660 mm) made of a galvanised, profiled steel sheet for the combination of accent lighting and general lighting; surface coated with polyester resin enamel; with rotary catches for rapid mounting to mounting rail. Housing colour silver grey/white aluminium RAL 9006; . Electrical connection by means of a fixed, 5-pin, quick-fit plug connector and a free choice of phases. Integrated guide for fast contacting. Suitable for luminaires with a 3-ph. track adapter (ET) from Regiolux, Global Trac, Eutrac, Iguzzini, Ivela, Powergear, Reggiani, Targetti, Zumtobel and 5-ph. track adapter (DALI) from Regiolux, Global Trac. The useful length of the 3-phase busbar with DALI enables the mounting of 3 spotty or 5 emphara spotlights. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

CHARACTERISTICS

Order number	19040000015
EAN number	4020863383351
Commodity code	94059900
Certification mark	IP 20, Protection class I, Indoor, CE

ELECTRICAL ENGINEERING

Mains voltage	230V/NaHz
---------------	-----------

MECHANICS

Housing colour	silver grey/white aluminium RAL 9006
Dimensions (LxWxDxH)	1532mm x 55mm x 44mm
Weight (net)	2.4kg
Type of installation	Mounting rail system installation, Ceiling-mounted light structure, Pendant light structure

Dimensions

L	1532 mm	Length
B	55 mm	Width
H	44 mm	Height

DEEP-LINK

<https://www.regiolux.de/en/article/19040000015>

