

Variable device mount functional module universal 3-phase track SRGVD

Device mount with integrated universal 3-phase track (useable length 660 mm) made of galvanised, profiled sheet steel for the combination of accent lighting and general lighting; surface coated with polyester resin enamel; with three rotary catches for rapid mounting to mounting rail. Can be variably positioned on the mounting rail. Housing colour traffic white RAL 9016; . Electrical connection by means of a 1m connection cable for variable device mount positioning with a 5-pin, quick-fit plug connector in the light run with free phase pre-selection. Suitable for luminaires with a 3-ph. track adapter (ET) from Regiolux, Global Trac, Eutrac, Iguzzini, Ivela, Powergear, Reggiani, Targetti, Zumtobel and 5-ph. track adapter (DALI) from Regiolux, Global Trac. The useful length of the 3-phase busbar with DALI enables the mounting of 3 spotty or 5 emphara spotlights. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system.

## CHARACTERISTICS

Order number	19040000030
EAN number	4020863421350
Commodity code	94059900
Certification mark	IP 20, Protection class I, Indoor, CE

## ELECTRICAL ENGINEERING

Mains voltage	230V/NaHz
---------------	-----------

## MECHANICS

Housing colour	traffic white RAL 9016
Dimensions (LxWxDxH)	1532mm x 55mm x 45mm
Weight (net)	2.5kg
Type of installation	Mounting rail system installation, Ceiling-mounted light structure, Pendant light structure

## Dimensions

L	1532 mm	Length
B	55 mm	Width
H	45 mm	Height

## DEEP-LINK

<https://www.regiolux.de/en/article/19040000030>

