

Assembly device mount

Universal assembly gear tray for surface-mounted luminaires alevo-AVAMP 1500-240/355 made of galvanised, profiled steel sheet, surface coated with polyester resin. Tool-free attachment with side lever catches for rapid fitting into the pre-wired SRT mounting rail. Housing colour traffic white RAL 9016; . Electrical connection by means of a 1m connection cable for variable device mount positioning with a 5-pin, quick-fit plug connector in the light run with free phase pre-selection. The assembly equipment support for alevo 130 is available on request. Planning note: 2 suspension points are required for each SRGVU. Please note the gear tray length of 1548mm. In the continuous row, the difference between the rail unit (1535mm) and SRGVU (1548mm) must be compensated for with an additional or longer rail and blind cover. Planning information - 2 suspension points are required per SRGVU; Please note the gear tray length of 1548mm: in the light run the difference between the rail unit (1535mm) and SRGVU (1548mm) must be compensated with an additional or longer rail with blank cover.

CHARACTERISTICS

Order number	19015500100
EAN number	4020863467457
Commodity code	94059900
Certification mark	IP 20, Protection class I, Indoor, CE

ELECTRICAL ENGINEERING

Mains voltage	230V/50Hz
---------------	-----------

MECHANICS

Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	1548mm x 55mm x 37mm
Weight (net)	0.94kg
Type of installation	Mounting rail system installation, Ceiling-mounted light structure, Pendant light structure

Dimensions

L	1548 mm	Length
B	55 mm	Width
H	37 mm	Height

DEEP-LINK

<https://www.regiolux.de/en/article/19015500100>

