

Mounting rail - Outfeed 11-pin

Torsion-resistant support rail made of galvanized, profiled sheet steel with zinc coating combined with polyester resin lacquer to ensure good corrosion protection; universal support rail suitable for light runs of all protection classes IP20 to IP64; Housing colour traffic white RAL 9016; . Heat-resistant, through-wiring with individual conductors installed in the factory. Including 3 current taps for electrical connection of the device mounts, in module 2250. 1 pre-scored knock-out at the top allows a direct feed via the mounting rail. Outfeed takes place without tools via plug-type connection terminals for the connection of flexible or rigid feed cables. Cover cap for start of light run is included in the scope of supply. for SRT Mounting rail for outfeed or infeed against the direction of running

CHARACTERISTICS

Order number	19200086100
EAN number	4020863424412
Commodity code	94059900
Certification mark	IP 20/40/54/64, Protection class I, Indoor, CE

ELECTRICAL ENGINEERING

Wiring	5x2.5 / 6x1.5mm ²
--------	------------------------------

MECHANICS

Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	2302mm x 63mm x 46mm
Weight (net)	2.625kg
Type of installation	Mounting rail system installation, Ceiling-mounted light structure, Pendant light structure, Ceiling-mounted mounting rail installation, Ceiling-mounted mounting rail installation on T-system, Pendulum mounting rail assembly on chain, Pendulum mounting rail installation on steel cable

Dimensions

L	2302 mm	Length
B	63 mm	Width
H	46 mm	Height

DEEP-LINK

<https://www.regiolux.de/en/article/19200086100>

