

Surface-mounted luminaire - Silky matt wall washer - direct asymmetrical distribution

Sheet steel housing, rectangular cross-section, plastic end faces with integrated light run connectors; Housing colour traffic white RAL 9016; Wallwasher characteristic with glare protection, Light distribution direct asymmetrical distribution by means of Silky matt wall washer of aluminium, self-engaging; neutral white light colour (840) with very good colour consistency and high colour rendering Ra=80. Electrical connection via 3-pole connection terminal with plug-in contacts.. Can be mounted on mounting rail. Necessary accessories available on request.

CHARACTERISTICS

Order number	65040024190
EAN number	4020863281275
Commodity code	94051190
Certification mark	IP 20, Protection class I, ENEC10 VDE, F, Indoor, CE
Impact resistance (IK rating)	IK03
Ambient temperatur	ta 25°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

ELECTRICAL ENGINEERING

Controller	Electronic driver (1 pcs.)
System output	29.1W
Mains voltage	230V/50Hz
Energy efficiency class/light source	B

LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
Colour tolerance (MacAdam)	3SDCM
Nominal luminous flux	3902lm
LED service life	50000h L80/B10 (Tq 25°C)
Luminaire luminous efficiency	134lm/W

MECHANICS


Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	1488mm x 140mm x 69mm
Weight (net)	4.292kg
Cable entry KE (X/Y)	75mm/-41mm
Type of installation	Ceiling-mounted single installation, Ceiling-mounted trunking installation, Pendulum mounting rail assembly on chain, Ceiling-mounted mounting rail installation, Ceiling-mounted mounting rail installation on T-system

Dimensions

L	1488 mm	Length
B	140 mm	Width
H	69 mm	Height
A1	1100 mm	Mounting distance single mounting
A3	376 mm	Mounting distance between luminaires in a light run arrangement
X	75 mm	Distance cable infeed to the center of the luminaire on the X-axis
Y	-41 mm	Distance cable infeed to the center of the luminaire on the Y-axis

DEEP-LINK

<https://www.regiolux.de/en/article/65040024190>



Reference	LED 3900lm 840
ηLB	100 %
Φ ↓/↑	100 % / 0 %

