

Diffuser luminaire - Opal diffuser - direct/indirect distribution

Round luminaire housing made of deep-drawn sheet steel; Housing colour traffic white RAL 9016; Light distribution direct/indirect distribution by means of Opal diffuser of acrylic glass, matt, smooth surface; round, domed acrylic glass diffuser, UGR (4H/8H) 20.8. Electrical connection via 3-pole connection terminal with plug-in contacts..

CHARACTERISTICS

Order number	25310134110
EAN number	402086333974
Commodity code	94051140
Certification mark	IP 40, Protection class I, Heat filament test 650°C, F, Indoor, CE
Impact resistance (IK rating)	IK02
Ambient temperatur	ta 25°C
Warranty period	5 years
State funding programs	BEG - Federal funding for efficient buildings (valid only for Germany)

ELECTRICAL ENGINEERING

Controller	Electronic driver (1 pcs.)
System output	18W
Mains voltage	230V/50Hz
Energy efficiency class/light source	D

LIGHTING TECHNOLOGY

Placement	LED, Colour rendering/Light colour CRI \geq 80 / 4000K
Colour tolerance (MacAdam)	3SDCM
Nominal luminous flux	2287lm
LED service life	50000h L80/B10 (Tq 25°C)
Luminaire luminous efficiency	124lm/W
UGR lat./long.	20.8 / 20.8

MECHANICS


Housing colour	traffic white RAL 9016
Dimensions (LxWxH/DxH)	373mm x 125mm
Weight (net)	1.4kg
Cable entry KE	See mounting instructions
Type of installation	Ceiling-mounted single installation, Wall mounting

Dimensions

H	125 mm	Height
D	373 mm	Diameter
A1	272 mm	Mounting distance single mounting
A1 alternativ	232 mm	Mounting distance single mounting (alternatively)

DEEP-LINK

<https://www.regiolum.de/en/article/25310134110>



Reference	LED 2300lm 840
η_{LB}	100 %
$\Phi_{\downarrow/\uparrow}$	86 % / 14 %
UGR lat./long.	20.8 / 20.8

